

SPECIFICATIONS



MOD. 74 Rev.01
Date: 05/12/2018
Page 1 di 2

5HV-302 2W SPEAKER UNIT WITH PUSHBUTTON

DESCRIPTION

Speaker unit designed for installation on the elevator car-top or in the pit

IMAGE



MAIN FEATURES

Independent audio digital speaker unit for 2W Esse-ti alarm systems

Two-way communication (full duplex)

Connection: [2-wire bus](#)

Power supply: [directly from the bus or via the 12 Vdc input](#)

Absorption in idle state: [20 mA](#)

Average absorption in alarm conversation mode: [50 mA](#)

Presence over the bus checked automatically by the alarm system

DIP switch for ID assignation over the bus

SPECIFICATIONS



MOD. 74 Rev.01
Date: 05/12/2018
Page 2 di 2

5HV-302 2W SPEAKER UNIT WITH PUSHBUTTON

Loudspeaker's volume setting: digital remotely adjustable

Microphone's volume setting: digital remotely adjustable

Emergency-call pushbutton

Plastic case

Dimensions (without terminal blocks): 117 x 64 x 17 mm

Dimensions (with terminal blocks): 117 x 73 x 17 mm

Weight: 77 g

Main terminal blocks:

- Power supply input: 12 Vdc
- Inputs for connecting external pushbuttons (voltage free contact pushbuttons NO/NC or powered pushbuttons)
- Customizable input: alarm / auxiliary / filter - (NO/NC)
- Outputs for connecting indicator lights (positive or negative pole)
- Digital bus

Terminal blocks for connecting a passive speaker unit:

- Output for connecting loudspeaker of passive speaker unit
- Input for connecting microphone of passive speaker unit or single microphone